

WL2

TWIN LEG 1.8M WEBBING LANYARD

TWIN LEG WEBBING LANYARD WITH SHOCK ABSORBER, CARABINER AND SCAFFOLD HOOK

The WL2 is a twin legged 1.8meter webbing lanyard with a CAB1 screwgate carabiner to connect to the users EN361 harness and two SCAF1 scaffold hook to attach to the anchoring point. The twin leg enables the user to be connected to an anchoring point at all times when moving between one anchor point to another. For example, when installing scaffolding or climbing. The Shock absorber is intended to reduce the force applied to the user in the event of a fall.

Must be used as part of a fall arrest system.



TECHNICAL INFORMATION

träegatech
PERFORM

ORDER REF. #	WL2
MATERIAL:	30mm polyester. Shock Absorber 45mm
SIZES AVAILABLE:	1.8 meter (both legs)
CONNECTOR OPENING:	CAB1 - 16mm SCAF1 - 52mm
MAX LOAD:	100 Kg
PACKING	
PER CASE: 	10 PIECES
PER PACK: 	1 PIECE PER BAG

CERTIFICATION BY:

SATRA, SATRA Technology Centre, Wyndham Way, Telford Way, Kettering, Northamptonshire, NN16 8SD. UK.
Notified body: 0321

Tested in accordance with:
EN 355:2002 / VG11 RFU SHEET 63

PRODUCT WEIGHT:	1.8kg
CARTON: N.W G.W	17 kg 18.5 kg



FREE-FALL
ARREST

If appropriate to the product, EC Declaration of Conformities, relevant certification and supporting documentation are available to access through your distributor, at the below web address(s) or by contacting Traega / UCI customer services.

This document and any other statement provided herein by or on behalf of Traega / UCI are given for informational purposes and do not constitute a contractual agreement nor warranty of merchantability. Traega / UCI assumes no responsibility for the suitability or adequacy of an end user's selection of product for a specific purpose. Always consult a suitable professional and the enclosed instructions before use.

»» enhanced performance



Phone: +44 (0)1902 451 451
Email: sales@ultimateindustrial.co.uk
Web: traega.co.uk | ultimateindustrial.co.uk