



## INSULATING HELMET WITH WHEEL RATCHET

### Safety Helmet with 6 Point Harness and Wheel Ratchet Adjustment

Industrial safety helmet made consisting of a moulded PP shell with a comfortable 6 point webbing harness inner to keep the user safe and secure. Wheel ratchet to the rear of the harness allows the helmet to be quickly and easily adjusted to fit the users head.

Fabric sweatband at the front of the harness absorbs any excess moisture during extended periods of use.

Rain gutter around the circumference of the helmet.

Available in White, Blue or Yellow



#### COMPATIBLE ACCESSORIES:

CS1 Chin Strap, EMH5 Earmuff, H86 Visor Carrier, H867 Visor Carrier, VCA85 PC Visor, VM85M Mesh Visor, HLT1 Helmet Liner

#### Colour Options



#### TECHNICAL INFORMATION

|                                                           |                                                                                                                        |              |
|-----------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------|--------------|
| ORDER REF #                                               | HD/HPEL/TER                                                                                                            |              |
| MATERIAL                                                  | Moulded PP Shell with Webbing                                                                                          |              |
| PACKING                                                   | PER PACK: 1                                                                                                            | PER CASE: 40 |
| SIZE                                                      | 55-62cm                                                                                                                |              |
| EU TYPE CERTIFICATION AND ONGOING CONFORMITY PERFORMED BY | BSI Group The Netherlands B.V., John M. Keynesplein 9, 1066 EP Amsterdam, Netherlands (Notified Body No. <b>2797</b> ) |              |

#### CERTIFICATION AND STANDARDS (SEE OVERLEAF FOR FURTHER DETAILS)

**EN397:2012 + A1:2012** - Mandatory Clauses With Optional:  
Lateral Deformation (LD)  
Electrical Insulation (440V a.c)

**EN50365 - Class 0 (1000V a.c)**



**Phone:** +44 (0)1902 451 451  
**Fax:** +44 (0)1902 451 271  
**Email:** sales@ultimateindustrial.co.uk  
**Web:** www.ultimateindustrial.co.uk



Ultimate  
Industrial

Leadership in  
PROTECTION.™

© 2020. **Ultimate Cleaners (Industrial) Ltd.**  
Victoria House, Colliery Road, Wolverhampton, WV1 2RD, UK.  
Registered in England No. 2035621



## FURTHER INFORMATION

**STORAGE / TRANSPORT:** Always store in clean, dry conditions and contain within the poly bag/box provided. Do not store in places subject to direct Sunlight or in contact with solvents.

**PRECAUTIONS BEFORE USE:** It is very important that the fitting instructions and recommendations are adhered to. If not the protection offered will be seriously impaired and serious injury may result. Further information should be sought from the manufacturer. The enclosed product information sheet should be read before use.

**CLEANING:** Clean with mild detergent. Do NOT use paints, solvents, chemicals, adhesives, petrol or similar substance on this helmet.

**DISINFECTION:** The parts of this product in contact with the skin should be disinfected (at least every 3 months) with a suitable disinfectant solution.

**CHEMICALS:** Certain chemicals may have a detrimental effect on contact with this product. If in doubt please check with your

### INSTRUCTIONS FOR USE:

**1.** Install the suspension to the helmet by inserting the 4 suspension hanger keys to the 4 key slots of the helmet. (Detailed assembly instructions are printed on the polybag.) If the chin strap is used, insert hooks into the two chin strap attachment holes on the side of the helmet.

**2.** This is a one size helmet and should be adjusted to fit by moving the pin to the appropriate ratchet hole at the nape of the neck.

**3.** If the chin strap is used, adjust the buckle until the helmet feels comfortable and snug to the head.

**NOTE:** Industrial safety helmets are intended primarily to protect the upper part of the wearer's head against injury from falling objects (and consequential brain injury and skull fracture). They are not intended to protect against molten metal splash. DO NOT MODIFY.

For more information about this product, or to access the Declaration of Conformity or Product Certification, visit;  
<https://www.ultimateindustrial.co.uk/product/1117-HPEL-TER>

If appropriate to the product, EC/EU Declaration of Conformities, relevant certification and supporting documentation are available to access through your distributor, at the above web address(s) or by contacting UCI customer services quoting the product reference code. This document and any other statement provided herein by or on behalf of UCI are given for informational purposes and do not constitute a contractual agreement nor warranty of merchantability. UCI assumes no responsibility for the suitability or adequacy of an end user's selection of product for a specific purpose. The manufacturer reserves the right to make any modifications it deems necessary. All product and company names are trademarks™ or registered® trademarks of their respective holders. © UCI Limited, 2020



**Phone:** +44 (0)1902 451 451  
**Fax:** +44 (0)1902 451 271  
**Email:** [sales@ultimateindustrial.co.uk](mailto:sales@ultimateindustrial.co.uk)  
**Web:** [www.ultimateindustrial.co.uk](http://www.ultimateindustrial.co.uk)

 **Ultimate  
Industrial** | *Leadership in  
PROTECTION.™*

© 2020. **Ultimate Cleaners (Industrial) Ltd.**  
Victoria House, Colliery Road, Wolverhampton, WV1 2RD, UK.  
Registered in England No. 2035621